

Bombilla lineal LED COB

78mm R7s 4.5W



| Referencia | 200650051 | 200650052 | 200650053 |
|------------------------|-------------------------|-------------------------|-------------------------|
| Descripción | Bombilla lineal LED COB | Bombilla lineal LED COB | Bombilla lineal LED COB |
| Potencia | 4.5W | 4.5W | 4.5W |
| Lúmenes (360°) | 480Lm | 480Lm | 480Lm |
| Casquillo | R7s | R7s | R7s |
| Ángulo apertura | 330° | 330° | 330° |
| Temperatura (K) | 3000K / Luz cálida | 4000K / Luz día | 6500K / Luz fría |
| Temperatura de trabajo | -20°C / +40°C | -20°C / +40°C | -20°C / +40°C |
| SDCM | <6 | <6 | <6 |
| Tiempo de encendido | <0.5s | <0.5s | <0.5s |
| Luz completa inmediata | 100% | 100% | 100% |
| CRI (Ra) | ≥80 | ≥80 | ≥80 |
| Hg | 0.0 | 0.0 | 0.0 |
| mA | 39mA | 39mA | 39mA |
| On / Off | 50.000 | 50.000 | 50.000 |
| IP | IP20 | IP20 | IP20 |
| Horas de vida | 15.000h. | 15.000h. | 15.000h. |
| Voltaje | 220-240V | 220-240V | 220-240V |
| Hz | 50/60Hz | 50/60Hz | 50/60Hz |
| Dimensión (ØxH) | 78mm | 78mm | 78mm |
| Embalaje | 10/200 | 10/200 | 10/200 |

Beneficios: reduce el consumo, el mantenimiento, no parpadea, protege el medio ambiente, no contiene mercurio.

Aplicaciones: casas, hoteles, restaurantes, supermercados, oficinas, negocios, bares.